



## W Series

# W242D

### ▶ Key Feature

- VESA Wall Frame Hole : 100 X 100 mm(W X H)
- Kensington lock : Yes
- Audio system : 2W X 2ch
- USB Hub : 2 X USB 2.0(Optional)
- Stand : Tilt (Pivot, Elevation – option)

### ▶ Specification

Display Panel	<b>Screen size</b>	24" Wide Diagonal
	<b>Type</b>	A-Si TFT Active Matrix
	<b>Viewing Angle( H/V)</b>	TN 160/ 160( CR≥10)
	<b>Pixel Pitch</b>	0.270 mm( H x V)
	<b>Resolution</b>	1920 x 1200
	<b>Response Time( ms)</b>	5ms( GTG )
	<b>Contrast Ratio</b>	10000:1 ( DCR)
	<b>Brightness</b>	300 cd/m <sup>2</sup>
Signal Input	<b>Active Display Size( H x V)</b>	518.4 x 324 mm
	<b>Display Color</b>	16.7 Million
	<b>Video</b>	R.G.B Analog DVI( HDCP )
	<b>Sync</b>	H/V - Separate TMDS Signal 15 pin D-sub DVI-D/ HDCP Connector
	<b>Connector</b>	
	<b>Cable</b>	PC Audio in > 1,500mm
	<b>Horizontal</b>	30 ~ 81kHz
	<b>Vertical</b>	56 ~ 76Hz
Max. Resolution (Analog)		1920 x 1200 @ 60Hz
Recommended Resolution		1920 x 1200 @ 60Hz
Plug-and-Play		VESA DDC 2B
Features	<b>VESA Wall Frame Hole</b>	100 x 100 mm( W X H)
	<b>Kensington lock</b>	Yes
	<b>Audio system</b>	2W x 2ch
	<b>USB Hub</b>	2 x USB 2.0( Option )
	<b>Stand</b>	Tilt-Stand
	<b>Option</b>	Pivot, Elevation
Power Management		VESA DPMS
Power	<b>Source</b>	100-240VAC
	<b>Consumption</b>	55W( Typ.)
	<b>Type</b>	Built-in
Emmissions Standard		-
Safety & Regulations	<b>Standard</b>	TUV/GS, UL/CUL, CB, CCC, Energy Star, EK, GOST, VCCI, C-Tick, FCC, CE, WEEE
	<b>Unit</b>	579 x 455 x 240 mm
Dimension (W x H x D)	<b>Packed</b>	656 x 538 x 241 mm
	<b>Unit</b>	8.4 kg
Weight	<b>Packed</b>	11.9 kg
	<b>20 ft. Container</b>	288 PCS
Loading Q'ty	<b>40 ft. Container</b>	648 PCS

All specifications are subject to change without prior notice