



Kodak EasyShare C433

Zoom Digital Camera

Point and shoot made fun and affordable.

Take the guesswork out of going digital with the Kodak EasyShare C433 zoom digital camera. With its user-friendly design and affordable price, everyday picture taking is a breeze. You'll have a host of convenient features to help capture and share quality pictures with family and friends. The C433 - small, uncomplicated, and affordable.

Beautiful picture quality

- Create amazing-quality prints up to 50 x 76 cm (20" x 30") with 4.0 MP
- Get closer to the action with 3X optical zoom and 5X advanced digital zoom
- Capture bright, beautiful color with exclusive Kodak color science
- Get consistently precise pictures with multi-zone and center-zone auto focus modes

Sharing made simple

- View your pictures with clarity on its 4.6 cm (1.8") indoor/outdoor color display



- Use the Favorites feature to keep your special pictures close
- Print, e-mail, and organize your photos with just one touch of the Kodak exclusive on-camera Share button
- Put life in motion with continuous VGA (640 x 480 at 14 fps) video featuring audio capture

Incredible ease of use

- Make great pictures even better with on-camera cropping, no need for a computer
- Don't miss a shot if your memory card becomes full, switch to in-camera memory quickly, thanks to the internal memory plus feature
- Get in the picture too with the two-shot self-timer
- Restore unintentionally deleted pictures with the undo-delete function
- Get great shots time after time using its 13 easy-to-access scene modes and 3 color modes
- Works with optional Kodak EasyShare G600 printer dock, Kodak EasyShare photo printer 500, Kodak EasyShare printer dock plus series 3, and Kodak EasyShare camera dock series 3

Kodak EasyShare C433

Zoom Digital Camera

Standard features

Sensor type	1/2.5" CCD
CCD total pixels	4.2 MP (2408x1758)
Effective pixels	4.0 MP (2336x1744)
Lens	3X optical, 36-108 mm (35 mm equiv.) f/2.7-4.9, with mechanical shutter and 2 step aperture
Zoom	3X optical zoom, 5X continuous digital zoom, 0.2X increments starting at 3X optical zoom
Lens barrier	built in lens barrier
Shutter speed	4-1/1400 second
LCD	4.6 cm (1.8") TFT display
Storage	16 MB* internal memory, SD/MMC card expansion slot

Auto focus

Type	TTL-AF
Focus range	normal: 0.6 m (2')-infinity; macro, wide: 0.1-0.7 m (4"-2.3'); macro, tele: 0.2-0.7 m (7.9"-2.3'); landscape: 10 m (32.8'-infinity)
Zones	multi-zone and center zone

Exposure control

ISO sensitivity	auto: ISO 80-200; manual: 80, 100, 200, 400, 800** selectable
Metering	TTL-AE, center weighted AE
Compensation	±2.0 EV with 1/2 EV steps
AE Lock	exposure is locked when shutter is pressed halfway
White balance	auto, daylight, tungsten, fluorescent

Flash

Range	0.6-3.5 m (2.0'-11.5') at wide, ISO 200; 0.6-2.0 m (2.0'-6.9') at tele, ISO 200
Modes	auto, fill, off, red eye

Shooting Specifications

Shooting modes	auto, SCN and video
Scene modes	portrait, sports, landscape, close-up, children, party, night portrait, beach, snow, fireworks, self portrait, backlight
Drive modes	single shot, self-timer (10 sec.), two-shot self-timer (10 sec.), delay shutter (2 sec.)
Click to capture	<0.7 sec., wide, (preview on)
Shot to shot	<2.5 sec.

Still capture

Still format	JPEG/EXIF v 2.21
Picture size	4.0 MP - best (2304x1728), prints up to 20"x30";
(recorded pixels)	3.5 MP - best 3:2 (2304x1536), optimized ratio for 4"x6" prints;
	3.1 MP - better (2048x1536), prints up to 8"x10";
	2.1 MP - good (1656x1242), prints up to 4"x6";
	1.1 MP - e-mail (1200x900), small prints

Color modes

Long time exposure	0.5-4 sec. (with 1/2 EV stop)
Review options	album, crop, slide show, multi up, copy, protect, image storage, picture/video info, set up menu
Editing	crop

Video capture

Format	QuickTime MOV with audio recording available
Quality	VGA (640x480) at 13 fps, QVGA (320x240) at 20 fps
Length	5, 15, 30 sec., and continuous based on memory capacity
Review options	album, slide show, multi-up, copy, protect, image storage, picture/video info, set up menu

Customization

Custom settings	set album, image storage location, camera sounds, auto power off, date and time, date stamp, video date display, language format
-----------------	--

Favorites

Favorites	slide show, multi-up, remove Favorites, set-up menu
-----------	---

Physical specifications

I/O interface	NTSC or PAL, selectable via dock connector, exclusive Kodak camera dock/printer dock interface, digital (USB 2.0) connector
Power	optional Kodak EasyShare docks with 1 Kodak Ni-MH rechargeable digital camera battery KAA2HR; Kodak alkaline batteries AA (supplied); 2 Kodak Ni-MH rechargeable digital camera batteries AA; 1 Kodak lithium digital camera battery CR-V3 ; 2 lithium batteries AA; Kodak Ni-MH 2100mAh battery pack, Kodak digital camera battery AA (ZR6), 3 volt DC input AC adapter

Tripod mount	1/4" standard
Dimensions	WxHxD: 91x69x35 mm (3.6"x2.7"x1.4")
Weight	130 g (4.6 oz.) without batteries and memory card

Compatibility

Dock compatibility	works with optional Kodak EasyShare G600 printer dock, and Kodak EasyShare camera dock series 3
Direct print	Kodak EasyShare photo printer 500, ImageLink print system compatible, PictBridge enabled
Software	works with Kodak EasyShare software

Service and support

Warranty	one year
----------	----------

Minimum system requirements

Windows	Windows 98, 98SE, ME, 2000 Professional, 2000 SP1, XP, 600 MHz processor or greater; Internet Explorer 6.0 or higher
Macintosh	Macintosh OS X 10.3 or higher

Minimum hardware requirements

128 MB RAM; 200 MB hard drive disk space available; CD-ROM drive, available USB port; color monitor, 800x600 display resolution, 16-bit minimum

Package contents

Kodak EasyShare C433 zoom digital camera
Kodak alkaline batteries AA or equivalent
USB cable
Wrist strap
Kodak EasyShare software
Getting Started Guide
Custom camera insert for optional Kodak EasyShare camera and printer docks

Ordering information

Kodak EasyShare C433 zoom digital camera (U.S. and Canada)xxx xxxx

Recommended accessories

Kodak EasyShare G600 printer dock	xxx xxxx
Kodak EasyShare photo printer 500	xxx xxxx
Kodak color cartridge and photo paper kit	xxx xxxx
Kodak EasyShare camera dock series 3	xxx xxxx
Kodak EasyShare picture viewer	xxx xxxx
Kodak SD memory cards 1 GB	xxx xxxx
512 MB	xxx xxxx
Digital picture storage kit	xxx xxxx
Picture guard kit	xxx xxxx
KAA2HR battery	xxx xxxx
K4500 charger	xxx xxxx
Kodak 8-in-1 card reader	xxx xxxx
Kodak small camera bag	xxx xxxx
Kodak travel kit	xxx xxxx
Kodak EasyShare starter kit	xxx xxxx

*16 MB internal memory/10 MB available for picture storage (1 MB equals one million bytes).

**ISO 800 is available only with 1.1 MP setting.

For more information on the Kodak EasyShare C433 zoom digital camera, visit www.kodak.com/go/easyshare



©Eastman Kodak Company, 2006. Kodak, EasyShare, ImageLink and the ImageLink print system logo are trademarks of Eastman Kodak Company. QuickTime and the QuickTime logo are trademarks or registered trademarks of Apple Computer, Inc. used under license therefrom. Product specifications subject to change without prior notice. Simulated screen images. IC-xxxx CAT No. xxx xxxx