

HT-S5100

7.1-Channel Home Entertainment Receiver/Speaker Package (with Dock for the iPod®)

BLACK SILVER



A Virtual Home Theater Powerhouse for High-Definition Video with iPod Playback and SIRIUS Connectivity

Looking for a home theater package with some genuine caliber? Then the HT-S5100 7.1-channel receiver/speaker package deserves your attention. As one of Onkyo's second-generation HDMI-compliant packages, the HT-S5100 gets the best out of high-definition video sources and lets you connect up to three 1080p sources for switching to one display. But a quality home theater package isn't defined by video alone. The HT-S5100 packs 1200 watts of stonking power, backed up by Audyssey room correction technologies, to create the perfect surround-sound environment. This is also Onkyo's first home theater package to come with a dedicated dock for iPod playback. With the right gear, you can even connect and subscribe to SIRIUS radio. And fleshing out the receiver is a 7.1 speaker package designed to sound even better than it looks when matched with the latest high-definition displays.

HT-R560 7.1-Channel A/V Surround Home Theater Receiver

- 130 Watts per Channel
- DTS®-ES™ Discrete/Matrix, DTS® Neo:6, DTS® 96/24, Dolby® Digital EX™, Dolby® Pro Logic® IIx
- HDMI Pass-Thru (1080p Compatible); 3 Inputs and 1 Output
- HDMI and Component Video (720p, 1080i); 2 Inputs and 1 Output Switching
- 4 Digital Inputs (2 Optical, 2 Coaxial)
- 3 S-Video Inputs and 2 Outputs
- 4 Composite Video Inputs and 2 Outputs
- 4 A/V Inputs and 1 Output
- 2 Audio Inputs and 1 Output
- Audyssey 2EQ to Correct Room Acoustic Problems and to Calibrate Speakers
- Audyssey Dynamic EQ for Loudness Correction
- H.C.P.S. (High Current Power Supply) Massive High Power Transformer
- WRAT (Wide Range Amplifier Technology)
- 192 kHz/24-Bit DACs for All Channels
- Advanced 32-Bit Processing DSP Chip
- Subwoofer Pre Out
- CinemaFILTER™
- A-Form Listening Mode Memory
- Optimum Gain Volume Circuitry
- Music Optimizer for Compressed Music Files
- Theater Dimensional Virtual Surround Function
- Double Bass Function

- Color-Coded 7.1-Multichannel Inputs (Receive 7.1 Surround Sound from Compatible Blu-ray Disc Players)
- Speaker A/B Drive
- Banana Plug-Compatible Speaker Posts (Except Speaker B)
- Crossover Adjustment at 40/50/60/80/100/120/150/200 Hz for Bass Management
- A/V Synchronization Function (Up to 100 ms in 20 ms Steps)
- SIRIUS™ Satellite Radio Through SiriusConnect Home Tuner Kit*
- 40 FM/AM/SIRIUS Radio Presets
- RI (Remote Interactive) Terminal
- Front Panel Auxiliary Input (for Camcorders, Game Consoles, etc.)
- Newly Designed Preprogrammed RI (Remote Interactive) Remote Control with Mode-Key LEDs

*SIRIUS requires separate purchase of subscription, compatible tuner and antenna.

DS-A1L* Dock for the iPod

- Recharges iPod
 - Superior Quality for Digital Music Files
 - Control with Onkyo Remote Control
- *Audio playback only

HTP-560 7.1-Channel Home Theater Speaker System

- **SKF-560F** 2-Way Bass Reflex Front Speakers
 - 5" (12 cm) OMF Cone Woofer
 - 1" (2.5 cm) Balanced Dome Tweeter

- Wood-Crafted Cabinet
- Max. Input Power: 130 W
- Magnetically Shielded

SKC-560C 2-Way Bass Reflex Center Speaker

- 3 1/4" (8 cm) OMF Cone Woofer x 2
- 1" (2.5 cm) Balanced Dome Tweeter
- Slimline Design for Easy Placement with HDTVs
- Max. Input Power: 130 W
- Magnetically Shielded

SKM-560S Full-Range Acoustic-Suspension Surround Speakers

- 3 1/4" (8 cm) Cone
- Wood-Crafted Cabinet
- Max. Input Power: 130 W

SKB-560 Full-Range Acoustic-Suspension Surround Back Speakers

- 3 1/4" (8 cm) Cone
- Wood-Crafted Cabinet
- Max. Input Power: 130 W

Note: The front/center speakers are gloss finished on the front. They also feature an impedance of 8 ohms, color-coded speaker terminals, wall-mounting capability and speaker cable.

SKW-560 Bass Reflex Powered Subwoofer

- 10" (25 cm) Cone
- Wood-Crafted Cabinet
- Max. Power: 290 W
- Down-firing

HT-S5100

7.1-Channel Home Entertainment Receiver/Speaker Package (with Dock for the iPod)

Connecting up to Three HDMI-Enabled Sources for HDMI Pass-Thru*

With three HDMI inputs and one output, the HT-R560 receiver is perfect for linking multiple HDMI-enabled sources to a high-definition display. With HDMI as the video conduit, the HT-R560 will effortlessly transport and enable the full potential of Blu-ray Disc, standard DVD video, HD broadcasts and gaming. HDMI will deliver 720p, 1080i and 1080p video signals from up to three sources for a single connection direct to your HDTV. Its 1080p pass-thru capability is perfect for enabling the highest possible video resolution.

*A separate audio connection is necessary to process multichannel audio.

Audio Playback from Your iPod with the Included DS-A1L Dock for the iPod

The ubiquitous iPod has revolutionized how we listen to and store our music. The HT-S5100 is the perfect platform for integrating virtually any iPod for audio playback. When connected to the Dock, you can control your iPod with the system's remote control. The Dock also recharges your iPod.

Music Optimizer to Support Compressed Digital Music Files

While MP3 or AAC files may sound fine on a portable digital player, the limitations of these compressed files can be exposed when played back through a home entertainment system. Onkyo has designed onboard Music Optimizer technology to improve the quality of compressed audio signals. Compressed music loses a substantial amount of bit information at higher frequencies, so the Music Optimizer technology works to overcome this limitation and enhance audio quality.

Correcting Room Distortion and Loudness with Audyssey 2EQ™ and Audyssey Dynamic EQ

The HT-S5100 uses Audyssey 2EQ to counter distortion created by walls, furniture, and other objects. This technology detects speaker distance, and then sets levels, delays, and crossovers, while also measuring room acoustics. Compared to one-position room correction systems, Audyssey 2EQ covers a much wider listening area. Moreover, it corrects problems in both frequency response and time domain (where most of the problems lie) across the entire listening area. The results are immediately obvious—a clear, well-balanced and natural sound.

After 2EQ calibration, Audyssey Dynamic EQ solves the problem of deteriorating sound quality at lower volumes. When volume is reduced on a standard home theater receiver, the bass disappears, voices change, and the surround soundstage becomes less enveloping. As volume is adjusted on the receiver, however, Dynamic EQ selects the best possible frequency response and surround levels moment-by-moment, resulting in an ideal listening experience at any volume level.

SIRIUS™ Satellite Radio Programming via SiriusConnect Home Tuner Kit*

By using the port on the back of the HT-R560, it's possible to access SIRIUS Satellite Radio. SIRIUS brings access to over 130 digital-quality channels, including 69 channels of 100% commercial-free music, plus exclusive channels of sports, news, talk, entertainment, traffic, weather, and data. The receiver has a SIRIUS jack on its rear that connects to an optional SiriusConnect™ home tuner kit.

*SIRIUS requires separate purchase of subscription, compatible tuner and antenna.

SPECIFICATIONS

RECEIVER SECTION

AMPLIFIER SECTION

Power Output

Front L/R	130 W/Channel
Center	130 W
Surround L/R	130 W/Channel
Surround Back L/R	130 W/Channel

Dynamic Power

	180 W (3 ohms, front)
	160 W (4 ohms, front)
	100 W (8 ohms, front)

THD (Total Harmonic Distortion)

	0.08% (Rated power)
--	---------------------

Damping Factor

	60 (Front, 1 kHz, 8 ohms)
--	---------------------------

Input Sensitivity and Impedance

	200 mV/47 k-ohms (Line)
--	-------------------------

Output Level and Impedance

	200 mV/2.2 k-ohms (Rec out)
--	-----------------------------

Frequency Response

	5 Hz–100 kHz/+1 dB, -3 dB
--	---------------------------

Tone Control

	±10 dB, 50 Hz (Bass)
	±10 dB, 20 kHz (Treble)

Signal-to-Noise Ratio

	100 dB (Line, IHF-A)
--	----------------------

Speaker Impedance

	8 ohms–16 ohms
--	----------------

VIDEO SECTION

Input Sensitivity/Output Level and Impedance

Video	1.0 Vp-p/75 ohms (Component and S-Video Y)
	0.7 Vp-p/75 ohms (Component Pb/Cs, Pr/Cr)
	0.28 Vp-p/75 ohms (S-Video C)
	1.0 Vp-p/75 ohms (Composite)

Component Video Frequency Response

	5 Hz–50 MHz, -3 dB
--	--------------------

TUNER SECTION

Tuning Frequency Range

FM	87.5 MHz–107.9 MHz
AM	530 kHz–1,710 kHz

FM/AM/SIRIUS Preset Memory

	40 stations
--	-------------

GENERAL

Power Supply

	AC 120 V, 60 Hz
--	-----------------

Power Consumption

	4.9 A
--	-------

Dimensions (W x H x D)

	17 1/8" x 5 1/8" x 14 13/16" (435 x 150 x 379 mm)
--	---

Weight

	21.63 lbs. (9.8 kg)
--	---------------------

SPEAKER SECTION

Speaker Type

Front/Center	2-way, bass reflex
Surround	Full-range, acoustic-suspension
Surround Back	Full-range, acoustic-suspension
Subwoofer	Bass reflex

Drivers

Front	5" (12 cm) cone woofer, 1" (2.5 cm) balanced-dome tweeter
Center	3 1/2" (8 cm) cone woofer x 2, 1" (2.5 cm) balanced-dome tweeter
Surround	3 1/2" (8 cm) cone
Surround Back	3 1/2" (8 cm) cone
Subwoofer	10" (25 cm) cone

Frequency Response

Front	35 Hz–50 kHz
Center	60 Hz–50 kHz
Surround	80 Hz–20 kHz
Surround Back	80 Hz–20 kHz
Subwoofer	25 Hz–150 Hz

Output Sound Pressure Level

Front	85 dB/W/m
Center	85 dB/W/m
Surround	81 dB/W/m
Surround Back	81 dB/W/m

Max. Input Power

Front/Center/Surround/ Surround Back	130 W
---	-------

Max. Output Power

Subwoofer	290 W
-----------	-------

Nominal Impedance

Front/Center/Surround/ Surround Back	8 ohms
---	--------

Input Impedance

Subwoofer	20 k-ohms
-----------	-----------

GENERAL

Dimensions (W x H x D)

Front	6 1/8" x 14 1/8" x 7 13/16" (155 x 371 x 198 mm)
Center	17 3/8" x 4 1/8" x 5 7/8" (436 x 105 x 132 mm)
Surround/ Surround Back	5 7/8" x 10 11/16" x 3 1/4" (151 x 271 x 96 mm)
Subwoofer	11 1/8" x 19 1/8" x 15 11/16" (283 x 498 x 399 mm)

Weight

Front	6.4 lbs. (2.9 kg)
Center	5.7 lbs. (2.6 kg)
Surround/ Surround Back	2.86 lbs. (1.3 kg)
Subwoofer	25.4 lbs. (11.5 kg)

Dock for the iPod

Dimensions (W x H x D)	4 13/16" x 2 7/8" x 4 13/16" (112 x 60 x 112 mm)
Weight	0.5 lbs. (220 g)

CARTON

Dimensions (W x H x D)	30 11/16" x 31 1/4" x 20 1/4" (779 x 794 x 514 mm)
Weight	90.8 lbs. (41.2 kg)

UPC CODE

(S)	751398008177
(B)	751398008160



HT-R560

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. Manufactured under license from Dolby Laboratories. Dolby and the double-D symbol are trademarks of Dolby Laboratories. DTS is a registered trademark and the DTS logos and Symbol are trademarks of DTS, Inc. Manufactured under license from Audyssey Laboratories. U.S. and foreign patents pending. 2EQ is a trademark of Audyssey Laboratories. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. "SIRIUS" and the SIRIUS dog logo are registered trademarks of SIRIUS Satellite Radio Inc. iPod is a trademark of Apple Inc., registered in the U.S. and other countries. CinemaFILTER is a trademark of Onkyo Corporation. All other trademarks and registered trademarks are the property of their respective holders.



Onkyo Corporation 2-1 Nishin-cho, Neyagawa-shi, Osaka 572-8540, JAPAN Tel: +81-72-831-8136 Fax: +81-72-833-5222 <http://www.onkyo.com/>
 Onkyo U.S.A. Corporation 18 Park Way, Upper Saddle River, N.J. 07458, U.S.A. Tel: +1-201-785-2600 Fax: +1-201-785-2650 <http://www.onkyousa.com/>
 Mexico: Representaciones de Audio, S.A. de C.V. Calle 10 No. 133 Col. Granjas San Antonio Del. Iztapalapa C.P. 09070 Mexico, D.F. MEXICO Tel: +525-55-697-9754 Fax: +525-55-582-5494
 Brazil: DISAC COMERCIAL LTDA Av. Brig. Faria Lima, No. 1.461-Torre SUL-cj 151-154 Sao Paulo-SP-Brazil CEP 01452-002 Tel: +55-11-3811-7272 Fax: +55-11-3811-7265 <http://www.disac.com.br>