

Key Features

- 6 ½" Mica Reinforced Woofer
- 6 ½" Enhanced H.O.P. Cone - Mid Woofer
- 3 ¼" Enhanced H.O.P. Cone - Mid Driver
- 1" Nano Fine® Balanced Dome Tweeter
- Sound Reproduction to 50kHz (for High Resolution Audio)
- 180W Maximum Input Power



Key Technologies

6 ½" Mica Reinforced Woofer

6 ½" Enhanced H.O.P. Cone - Mid Woofer

3 ¼" Enhanced H.O.P. Cone - Mid Driver

1" Nano Fine® Balanced Dome Tweeter

Sound Reproduction to 50kHz (for High Resolution Audio)

180W Maximum Input Power

SS-F6000

Floor Standing Speaker

Specifications

Audio

Impedance: 8 Ohms

Power

Power Requirements: 40 - 50,000 Hz

Speaker

Frequency Response: 40 - 50,000 Hz

Impedance: 8 Ohms

Power Requirements: 180W

Quantity (Packaged): 2

Quantity of Tweeters: 1

Sensitivity: 89 dB

Speaker Terminal Type: Binding Post

Woofer Size(s): 6 1/2" (16cm) x 2

Quantity of Woofer(s): 2

Mid Range Size(s): 3 1/4" (8 cm)

Tweeter Size: 1" (2.5 cm)

Service and Warranty Information

Limited Warranty Term: 1 Year Parts / 1 Year Labor

Dimensions

Weight: 26 lb, 13 oz (12.2kg) each

Measurements: 8 7/16 x 37 3/8 x 10 1/4" (215 x 950x 200mm) each

UPC Code: 027242712812

©2007 Sony Electronics Inc. Reproduction in whole or in part without express written permission is prohibited. Sony and Nano Fine are trademarks of Sony. All other trademarks are property of their respective owners. Features and specifications are subject to change without notice. Non-metric weights and measures are approximate.



Please visit the Dealer Network for current information at www.sony.com/dn