

VA1703wb

17" VALUE SERIES WIDESCREEN LCD WITH 8MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13346-00B-01/07] VA1703wb-1

LCD	Type	17" color TFT active matrix SXGA LCD
	Display Area	14.4" horizontal x 9.0" vertical; 17.0" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	500:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life, 30,000 hrs. (typ)
VIDEO INPUT	Brightness	250 cd/m2 (typ)
	Panel Surface	Anti-glare
	Analog	RGB analog (75 ohms, 0.7 Vp-p)
COMPATIBILITY	Frequency	F _H : 24~70kHz, F _V : 50~75Hz
	Sync	H/V separated (TTL)
CONNECTOR	PC	VGA up to 1440x900 non-interlaced
	Mac**	Power Mac™ G3/G4/G5 up to 1440x900
POWER	Analog	15-pin mini D-sub
	Power	3-pin AC plug (CEE22)
CONTROLS	Voltage	AC 100~240V (universal), 50/60Hz (auto switch)
	Consumption	21W (typ)
OPERATING CONDITIONS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, contrast, brightness, ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information (resolution, H-freq, V-freq, pixel clock, model number, serial number, web site), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
DIMENSIONS	Temperature	32~104°F (0~40°C)
	Humidity	10~90% (non-condensing)
WEIGHT	Physical with stand	16.0" x 14.7" x 8.3" (407mm x 375mm x 210mm)
	Physical without stand	16.0" x 11.5" x 2.5" (407mm x 293mm x 63mm)
REGULATIONS	Net with stand	8.2 lb. (3.7 kg)
	Net without stand	6.38 lb. (2.9 kg)
	Gross with stand	11.2 lb. (5.1 kg)
RECYCLE/DISPOSAL	UL, cUL, FCC-B, CB, CE, NOM, TUV/GS, TUV/ERGO (covers ISO13406-2), MPR II, BSMI, CCC, ENERGY STAR®, PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO	
POWER MANAGEMENT	The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.	
PACKAGE CONTENTS	Meets MPR II and ENERGY STAR® standards	
WARRANTY	LCD display, video cable, power cable, Quick Start Guide, ViewSonic Wizard	
	Three-year limited warranty on parts, labor and backlight.	

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com